

NAME

bp-save-history - save bpipe field history

DESCRIPTION

bp-save-history operates on **bpipe** formatted data streams.

It saves history by transforming scalar fields into one dimensional arrays (stacks), and duplicating the current value of the field onto the stack. If a field is already a one-dimensional array, it does not increase its dimensionality.

Note that if the intrinsic datum stored in a field has non-zero dimensionality, **bp-save-history** cannot handle it, and will exit with error. It assumes that all one-dimensional arrays are history stacks of zero dimension data.

PARAMETERS

bp-save-history uses an IRAF-compatible parameter interface.

The following parameters are available:

input *file*

Input ray stream. If the filename is the string `stdin`, it reads the UNIX standard input stream.

output *file*

Output ray stream. If the filename is the string `stdout`, it writes to the UNIX standard output stream.

fields *float*

A comma separated list of fields to save. If **fields** is set to **%all**, all fields are saved.

version *boolean*

Print out **bp-save-history**'s version and exit.

help *boolean*

Print out help and exit.

COPYRIGHT & LICENSE

Copyright 2013 Smithsonian Astrophysical Observatory

This software is released under the GNU General Public License, either version 3 of the License, or (at // your option) any later version.. You may find a copy at

<http://www.fsf.org/copyleft/gpl.html>

AUTHOR

Diab Jerius <djerius@cfa.harvard.edu>