

URL: http://cxc.harvard.edu/ciao3.4/sherpa-module.html

Last modified: December 2006

Context: sherpa

AHELP for CIAO 3.4

sherpa-module

Jump to: Description CHANGES IN CIAO 3.2 Bugs See Also

Synopsis

Accessing data with the Sherpa/S-Lang module functions.

Description

Sherpa, the modeling and fitting application of the Chandra Interactive Analysis of Observations (CIAO) software package, was originally designed as a 'black box': data were to be input from a file, and analyzed, with results possibly written out to disk; however, the data themselves were not to be manipulated once input. The embedding of the S–Lang scripting language into Sherpa allows us to move from this 'black box' paradigm to one in which numeric data can be freely moved into and out of the box, and freely manipulated outside that box (e.g., with S–Lang functions). This movement of data requires the new functionality of the Sherpa/S–Lang module.

There are six principal types of Sherpa/S-Lang module functions, differentiated by prefix:

Summary of Sherpa/S-Lang Module Function Types

Name	Description	
get	Functions for retrieving data and settings from Sherpa	
is	Query functions	
list	Functions for retrieving string-based information from Sherpa and presenting it in tabular form	
load	Functions for loading datasets, file-based models, etc., into Sherpa	
	An extension of get functions designed to run a computationally intensive task (e.g., PROJECTION) and after completion return numerical information to the user. (Each run function has a corresponding get function, which simply retrieves the information from the most recent previous run.)	
set	Functions for putting data into Sherpa, or changing settings	

Miscellaneous functions which are not classified into one of the six types above include:

Other Sherpa/S-Lang Module Functions

Name	Description
compute_errors	Estimate errors for data given the current Sherpa statistic setting
compute_statistic	Compute a statistic given a data and model array, and the current Sherpa statistic

sherpa-module 1

Ahelp: sherpa-module - CIAO 3.4

	setting
create_model create_inst_model	Create a new instantiation of a Sherpa model
restore_unc	Restore the default settings of the configuration variable sherpa.unc
restore_proj	Restore the default settings of the configuration variable sherpa.proj
restore_cov	Restore the default settings of the configuration variable sherpa.cov
restore_intunc	Restore the default settings of the configuration variable sherpa.intunc
restore_intproj	Restore the default settings of the configuration variable sherpa.intproj
restore_regunc	Restore the default settings of the configuration variable sherpa.regunc
restore_regproj	Restore the default settings of the configuration variable sherpa.regproj

CHANGES IN CIAO 3.2

The Sherpa module can now be loaded by using the require("sherpa"); statement, although the previous method (loading with the import command) still works.

Bugs

See the Sherpa bug pages online for an up-to-date listing of known bugs.

See Also

chandra

guide

sherpa

bye, calc kcorr, dataspace, dcounts, dollarsign, echo, eflux, eqwidth, erase, flux, get, get dcounts sum, get dir, get eflux, get eqwidth, get filename, get flux2d, get flux str, get lfactorial, get mcounts sum, get pflux, get source components, get verbose, groupbycounts, guess, is, journal, list, list par, mcounts, numbersign, paramest, plot eprof, plot rprof, prompt, reset, run, set, set analysis, set axes, set coord, set dataspace, set dir, set verbose, setplot, sherpa plotfns, sherpa utils, show, simspec, use, version

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL: http://cxc.harvard.edu/ciao3.4/sherpa-module.html
Last modified: December 2006