

ACIS Report

1. Overall Status of the Instrument

2. Update on Controlling the FP Temperature

ACIS Ops Team

1

Paul Plucinsky

CUC September 2007

CXC



<u>1. Overall Status of the Instrument</u>


- Instrument continues to work well, no failures to report, no new degradations to report
- No anomalies since the last meeting of the CUC (Yeah !!)
- CTI increasing consistent with expectations, FI CCDs 2.3%/yr, BI CCDs 1.0%/yr
- Contaminant continues to accumulate slowly, recent work by Herman Marshall on the C, O, F edges vs. time included in the calibration report
- Use of Optional CCDs for observations at forward-Sun pitch angles - only three 6-CCD observations have been reduced to 5-CCD observations, so proactive scheduling is minimizing the science impact
- Thermal issues are still the most challenging, observations with pitch angles between 135-180 lead to heating of the ACIS detector housing and hence the focal plane




2. Controlling the ACIS FP Temperature

Bissell (NGST), blue points 8 hr averages, red line 30 day running average

CXC



Paul Plucinsky



CUC September 2007

Paul Plucinsky


(C) (C) (C)



NORTHROP GRUMMAN


Space Technology

Current Temperature Dependencies vs Sun Pitch




5





enter

<u>ACIS FP Temp vs Pitch Angle, DH Heater Power, Earth Solid Angle</u>





Possible Responses to a Warmer FP Temperature

1) Turn off the ACIS DH heater and the SIM FA6 heater

PRO: maintains calibration and best performance of the CCDs

CON: DH temperature is unregulated

2) Impose new MP constraints on duration of time spent at pitch angles >120 PRO: stable DH temperature for Fid Lights

CON: adds yet another constraint to an already tightly constrained schedule


3) Operate at a higher FP temperature

PRO: easy for operations and MP

CON: degrades CCD performance, requires a lengthy recalibration

Option #1 is the preferred option

NOTE ** ACIS FP temperature set point will remain at -119.7 C **





Analysis by Joe Vogrin (NGST) and Neil Tice (LMA):

"Chandra ISIM Thermal Study to Lower ACIS Focal Plane Temperature"

- the ACIS and SIM temperatures were modeled for a range of pitch angles between 45 and 172 in 10 degree steps

- study indicates that the ACIS DH temperature side A/B will range from

-71/-69 C at pitch=45 to -67/-66 C at pitch=145 (current temperatures are

-62.4/-59.9 C)

- steady-state solution, these are equilibrium temperatures, whether they will be reached on-orbit depends on the time constants (which can be long) and the duration of time the heaters are off
- study indicates that the FP temperature will be up to 3.0 degrees colder at a pitch angle of 145. This is a large enough difference to significantly improve the performance of the CCDs.
- study indicates that ~2.5 degrees of the improvement comes from a lower DH temperature

Paul Plucinsky

CUC September 2007




Two Proposed Tests Approved by the Flight Directors Board

Tests scheduled for tail-Sun orientations in which the DH temperature should not drop below -67/-66 (-71/-69) C if the SIM is at the ACIS (HRC) observing position

- 1) Turn off the ACIS DH heater during a perigee passage and HRC calibration observations just after perigee, turn on 2 hr before first outbound ACIS science observation starts, execute in the stored command load (~70 ks to cool), (17 September 2007)
- 2) Turn off the ACIS DH heater during an 48 ks observation (cool for 40 ks) of the CDF-South, (23 September 2007)
 - -- as the ACIS DH contracts/expands as it cools/warms the Fid Lights will move by an amount which may be large enough to affect the aspect
 - -- Tom Aldcroft believes that he can account for this apparent shift of the Fid Lights, Tom will analyze the results and attempt to reconstruct the aspect



CXC





Implementation: Future Plans

-- *If* the verification test and the test during a perigee passage are successful, we would like to turn off the DH heater for all perigee passages, success criteria:

Verification test - receive expected TLM verifiers that heater turns off and on

Perigee test - DH cools below -60 C but not down to -72 C & warms to -60 C in 2 hr

-- *If* the test during the CDF-S test is successful, success criteria: Absolute astrometry - 0.4 arcsec error

Image reconstruction - demonstrate that Enclosed Counts Fractions are statisically identical to previous observations

- 1) Schedule additional tests during remaining CDF-South observations
- 2) Proceed with implementation of DS SW to reconstruct aspect with a variable DH temperature
- **3)** Schedule tests at different pitch angles and work gradually to more forward-Sun attitudes to characterize cooling rates in different attitudes
- 4) Return to the FDB to ask to turn off the DH heater for good once the SW is available

-- Continue to investigate the option of turning off the SIM FA6 heater to gain more control on the ACIS FP temperature

Paul Plucinsky

CUC September 2007