



---

AHELP for CIAO 3.4

## `__push_args`

Context: [slangrtl](#)

Jump to: [Description](#) [See Also](#)

---

### Synopsis

Remove *n* function arguments onto the stack

### Syntax

```
__push_args (Struct_Type args);
```

### Description

This function together with the companion function `__pop_args` is useful for passing the arguments of one function to another. See the description of `__pop_args` for more information.

### See Also

*slangrtl*

[\\_\\_class\\_id](#), [\\_\\_class\\_type](#), [\\_\\_eqs](#), [\\_\\_get\\_reference](#), [\\_\\_is\\_initialized](#), [\\_\\_pop\\_args](#), [\\_\\_nargs](#), [\\_\\_pop\\_n](#), [\\_\\_stk\\_roll](#), [\\_\\_typeof](#), [array\\_info](#), [dup](#), [is\\_defined](#), [is\\_struct\\_type](#), [length](#), [pop](#), [typecast](#), [typeof](#)

---

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory.  
60 Garden Street, Cambridge, MA 02138 USA.  
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:  
[http://cxc.harvard.edu/ciao3.4/\\_push\\_args.tm.html](http://cxc.harvard.edu/ciao3.4/_push_args.tm.html)  
Last modified: December 2006

