



AHELP for CIAO 3.4

get_dcounts_sum

Context: [sherpa](#)

Jump to: [Description](#) [Example](#) [Bugs](#) [See Also](#)

Synopsis

Calculates the sum of observed counts in source and background datasets using module functions in Sherpa.

Syntax

```
Struct_Type get_dcounts_sum(Struct_Type)
Struct_Type get_bdccounts_sum(Struct_Type)
Struct_Type get_net_counts_sum(Struct_Type)
Struct_Type get_dcounts_sum([Integer_Type[, {Float_Type | Array_Type}]] )
Struct_Type get_bdccounts_sum([Integer_Type[, {Float_Type | Array_Type}]] )
Struct_Type get_net_counts_sum([Integer_Type[, {Float_Type |
Array_Type}]] )
```

Error Return Values: NULL

Arguments:

- (1) Structure of form returned by `get_flux_str`; or
- (1) Dataset number (default 1)
- (2) Evaluation point, or lower-upper bounds (default use all data)
- (3) Model component or stack name (default use all appropriate models)

Description

These functions retrieve the summation of observed data counts. `get_net_counts_sum` retrieves the summation of observed source, i.e., background-subtracted counts. Note that this function does not require the data to be background-subtracted.

The output of `get_flux_str()`, a structure, can be used as input to `get_dcounts_sum()` and `get_bdccounts_sum()`. One would retrieve this default structure, modify its field values, and pass it to `get_dcounts_sum()` et al. See the example below.

Note that numerical arguments are interpreted using Sherpa's current ANALYSIS setting.

The structure output by these functions contains the following fields:

get_dcounts_sum Structure Fields

Field	Description
dataset	the dataset for which the counts summation is evaluated
range	the single point at which the counts is determined, or the range over which the counts are summed; if NULL, the summation is done over the entire dataset range
comp	NULL for these functions
value	the summation of counts
units	NULL for these functions

See the related Sherpa command DCOUNTS for more information.

Example

Determine the number of counts in a dataset between 2 and 10 keV:

```

sherpa> foo = get_flux_str()
sherpa> print(foo)
dataset          = 1
range            = NULL
comp             = NULL
sherpa> foo.range = [2,10]
sherpa> print(get_dcounts_sum(foo).value)
518
sherpa> print(get_net_counts_sum(foo).value)
279.221
    
```

Bugs

See the [Sherpa bug pages](#) online for an up-to-date listing of known bugs.

See Also

chandra

[guide](#)

sherpa

[bye](#), [calc_kcorr](#), [dataspace](#), [dcounts](#), [dollarsign](#), [echo](#), [eflux](#), [eqwidth](#), [erase](#), [flux](#), [get](#), [get_dir](#), [get_eflux](#), [get_eqwidth](#), [get_filename](#), [get_flux2d](#), [get_flux_str](#), [get_lfactorial](#), [get_mcounts_sum](#), [get_pflux](#), [get_source_components](#), [get_verbose](#), [groupbycounts](#), [guess](#), [is](#), [journal](#), [list](#), [list_par](#), [mcounts](#), [numbersign](#), [paramest](#), [plot_eprof](#), [plot_rprof](#), [prompt](#), [reset](#), [run](#), [set](#), [set_analysis](#), [set_axes](#), [set_coord](#), [set_dataspace](#), [set_dir](#), [set_verbose](#), [setplot](#), [sherpa-module](#), [sherpa_plotfns](#), [sherpa_utils](#), [show](#), [simspec](#), [use](#), [version](#)

Ahelp: get_dcounts_sum – CIAO 3.4

60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

Last modified: December 2006

