



AHELP for CIAO 3.4

redo

Context: [chips](#)*Jump to:* [Examples](#) [Bugs](#) [See Also](#)

Synopsis

Redoes the most recently undone plotting command.

Syntax

```
chips> REDO [#]
```

where # is an integer number of commands to be redone.

Example 1

```
chips> CURVE data/example.dat  
chips> LIMITS X 5.0 15.0  
chips> UNDO  
chips> REDO
```

A curve is plotted and the limits of the X-axis are changed. The UNDO command restores the limit to their original defaults. The REDO command then redoes the most recently undone command, thus changing the X-axis limits once again.

Example 2

```
chips> CURVE data/example.dat  
chips> LIMITS X 5.0 15.0  
chips> LIMITS Y 10.0 15.0  
chips> AXES BLUE  
chips> LIMITS Y 10.0 25.0  
chips> UNDO 3  
chips> REDO 1
```

A curve is plotted and the limits of both axes are changed. They are colored blue, then the Y-axis limits are changed again. The UNDO command backtracks through the previous three commands (in the order they are undone: LIMITS Y 10.0 25.0, AXES BLUE, LIMITS Y 10.0 15.0). The REDO command then redoes the most recently undone command (LIMITS Y 10.0 15.0), leaving the final plot with white axes and limits of x=5:15, y=10:15.

Bugs

See the [bugs page for ChIPS](#) on the CIAO website for an up-to-date listing of known bugs.

See Also

chips

[batch](#), [browse](#), [clear](#), [delete](#), [exit](#), [info](#), [list](#), [pickpoints](#), [redraw](#), [type](#), [undo](#), [verbose](#)

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
<http://cxc.harvard.edu/ciao3.4/redo.html>
Last modified: December 2006