



AHELP for CIAO 3.4

ds9_view

Context: [ds9](#)

Jump to: [Description](#) [NOTES](#) [See Also](#)

Synopsis

Launch DS9 with file or image pixel array

Syntax

```
ds9_view( filename [, ds9_arg1, ds9_arg2, ... ] )
ds9_view( image_pixel_array [, ds9_arg1, ds9_arg2, ... ] )
```

Description

A convenience function, which issues a `ds9_launch()` command followed by `ds9_put_file()` or `ds9_put_array()` as appropriate.

NOTES

All parameters after the first will be interpreted as DS(command–line arguments.

See Also

ds9

[ds9 center](#), [ds9 clear](#), [ds9 get array](#), [ds9 get cmap](#), [ds9 get coords](#), [ds9 get crosshair](#), [ds9 get file](#), [ds9 get regions](#), [ds9 get scale](#), [ds9 get zoom](#), [ds9 launch](#), [ds9 pan](#), [ds9 put array](#), [ds9 put crosshair](#), [ds9 put file](#), [ds9 put regions](#), [ds9 put wcs](#), [ds9 put wcs keys](#), [ds9 put wcs struct](#), [ds9 quit](#), [ds9 set cmap](#), [ds9 set scale](#), [ds9 set zoom](#)

modules

[ds9](#)

