



AHELP for CIAO 3.4

strup

Context: [slangrtl](#)

Jump to: [Description](#) [Example](#) [See Also](#)

Synopsis

Convert a string to uppercase

Syntax

```
String_Typestrup (String_Type s)
```

Description

The `strup` function takes a string `s` and returns another string identical to `s` except that all lower case characters that comprise `s` will be converted to upper case.

Example

The function

```
define Strcmp (a, b)
{
    return strcmp (strup (a), strup (b));
}
```

performs a case-insensitive comparison operation of two strings by converting them to upper case first.

See Also

slangrtl

[array_sort](#), [define_case](#), [strcmp](#), [strcompress](#), [string_match](#), [strlow](#), [strncmp](#), [strreplace](#), [strtrans](#), [strtrim](#), [strtrim_beg](#), [strtrim_end](#), [tolower](#), [toupper](#)

Ahelp: strup – CIAO 3.4

The Chandra X-Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory.
60 Garden Street, Cambridge, MA 02138 USA.
Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL:
<http://cxc.harvard.edu/ciao3.4/strup.tm.html>
Last modified: December 2006