

AHELP for CIAO 3.4

xspexrav

Context: sherpa

Jump to: Description Bugs See Also

Synopsis

Exponentially cutoff power law reflected from neutral matter. XSpec model.

Description

Exponentially cutoff power law spectrum reflected from neutral material (Magdziarz and Zdziarski 1995, MNRAS, 273, 837). The output spectrum is the sum of an e–folded power law and the reflection component.

The reflection component alone can be obtained for relRefl < 0. Then the actual reflection normalization is |relRefl|. Note that you then need to change the limits of relRefl to exclude zero (as then the direct component appears). If foldE = 0 there is no cutoff in the power law.

The metal and iron abundance are variable with respect to those defined by the xspecabundan command. The opacities are from Balucinska and McCammon (ApJ 400, 699 and 1994, private communication). H and He are assumed to be fully ionized.

Number	Name	Description
1	PhoIndx	power law photon index, N_E prop. to E^(-PhoIndx)
2	TOIGE	the e-folding energy in keV (if foldE=0, there is no cutoff; change the lower limit for that)
3	reiketi	reflection scaling factor; if < 0, there is no direct component; relRefl=1 for isotropic source above disk
4	Redshift	redshift, z
5	abund	abundance of elements heavier than He relative to that defined by xspecabundan
6	FeAbund	iron abundance relative to that defined by xspecabundan
7	cosIncl	cosine of inclination angle
8	norm	photon flux at 1 keV (photons/keV/cm^2/s) of the power law only in the observed frame

xspexrav Parameters

This information is taken from the <u>XSpec User's Guide</u>. Version 11.3.1 of the XSpec models is supplied with CIAO 3.2.

Bugs

For a list of known bugs and issues with the XSPEC models, please visit the XSPEC bugs page.

See Also

sherpa

atten, bbody, bbodyfreg, beta1d, beta2d, box1d, box2d, bp11d, const1d, const2d, cos, delta1d, delta2d, dered, devaucouleurs, edge, erf, erfc, farf, farf2d, fpsf, fpsf1d, frmf, gauss1d, gauss2d, gridmodel, hubble, jdpileup, linebroad, lorentz1d, lorentz2d, models, nbeta, ngauss1d, poisson, polynom1d, polynom2d, powlaw1d, ptsrc1d, ptsrc2d, rsp, rsp2d, schechter, shexp, shexp10, shlog10, shloge, sin, sqrt, stephild, steplold, tan, tpsf, tpsfld, usermodel, xs, xsabsori, xsacisabs, xsapec, xsbapec, xsbbody, xsbbodyrad, xsbexrav, xsbexriv, xsbknpower, xsbmc, xsbremss, xsbvapec, xsc6mekl, xsc6pmekl, xsc6pvmkl, xsc6vmekl, xscabs, xscemekl, xscevmkl, xscflow, xscompbb, xscompls, xscompst, xscomptt, xsconstant, xscutoffpl, xscyclabs, xsdisk, xsdiskbb, xsdiskline, xsdiskm, xsdisko, xsdiskpn, xsdust, xsedge, xsequil, xsexpabs, xsexpdec, xsexpfac, xsgabs, xsgaussian, xsgnei, xsgrad, xsgrbm, xshighecut, xshrefl, xslaor, xslorentz, xsmeka, xsmekal, xsmkcflow, xsnei, xsnotch, xsnpshock, xsnsa, xsnteea, xspcfabs, xspegpwrlw, xspexriv, xsphabs, xsplabs, xsplcabs, xsposm, xspowerlaw, xspshock, xspwab, xsraymond, xsredden, xsredge, xsrefsch, xssedov, xssmedge, xsspline, xssrcut, xssresc, xssssice, xsstep, xstbabs, xstbgrain, xstbyarabs, xsuvred, xsvapec, xsvarabs, xsvbremss, xsvequil, xsvgnei, xsvmcflow, xsvmeka, xsvmekal, xsvnei, xsvnpshock, xsvphabs, xsvpshock, xsvraymond, xsvsedov, xswabs, xswndabs, xsxion, xszbbody, xszbremss, xszedge, xszgauss, xszhighect, xszpcfabs, xszphabs, xszpowerlw, xsztbabs, xszvarabs, xszvfeabs, xszvphabs, xszwabs, xszwndabs

slang

<u>usermodel</u>

The Chandra X–Ray Center (CXC) is operated for NASA by the Smithsonian Astrophysical Observatory. 60 Garden Street, Cambridge, MA 02138 USA. Smithsonian Institution, Copyright © 1998–2006. All rights reserved.

URL: <u>http://cxc.harvard.edu/ciao3.4/xspexrav.html</u> Last modified: December 2006